



EcoTouch[®] Insulation for Metal Utility Blanket with PureFiber[®] Technology

Product Data Sheet



Physical Properties

Property	Test Method	Value
Combustibility	ASTM E136, CAN/ULC S114	Noncombustible
Nominal Density	ASTM C167	0.8 PCF
Fire Hazard Classification	ASTM E84, UL 723, CAN/ULC S102	FHC 25/50
Moisture Absorption	ASTM C1104	<2% by weight
Fungi Resistance	ASTM C1338	No growth greater than comparative item

I. The surface burning characteristics of these products have been determined in accordance with ASTM E84, UL 723, or CAN/ULC S102. These standards should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest 5 rating.

Description

Owens Corning[™] EcoTouch[®] Insulation for Metal Building Utility Blanket with PureFiber[®] Technology is an unfaced light density fibrous glass blanket. The product is designed to be laminated with a variety of facings and is used for condensation and noise control in metal buildings. The product is available in rolls with widths of 36", 48" and 72" at a nominal product thickness of 2".

Key Features

- Verified formaldehyde-free¹
- Soft to the touch
- Uses a minimum of 65% recycled content.
- GREENGUARD Gold Certified
- Easy to handle
- Excellent recovery provides outstanding thermal and acoustical performance

Thermal Resistance

Inches	Thickness		R-Value ¹	RSI Value ¹
	Inches	mm		
2		51	7.0	1.23

I. Pre-lamination values

Product Application

After the product is laminated with an appropriate facing, the insulation is typically installed in a single layer between the structural members (purlins for roofs and girts for walls) and the exterior panels. In most cases, the product is installed over and perpendicular to the structural members with the facing towards the interior of the structure.

Care should be taken not to overstretch the insulation material as excess compression can reduce the insulation's thermal performance. All seams should be sealed to help maintain a continuous vapor retarder.

EcoTouch[®] Insulation for Metal Building Utility Blanket can also be used over the purlins in roof systems that utilize a primary layer of insulation between the purlins.

Owens Corning[™] EcoTouch[®] Insulation for Metal Building Utility Blanket is fabricated and distributed by a nationwide network of independent laminators assuring prompt service and delivery. Contact your Owens Corning Insulating Systems representative for the names of insulation laminators servicing your area.

Standards, Codes Compliance

- CAN/ULC - S702—Standard for Mineral Fiber Thermal Insulation for Buildings-Type I.
- ASTM C665—Standard Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction; Type I.

¹ Applies to the insulation component only.



EcoTouch[®] Insulation for Metal Utility Blanket with PureFiber[®] Technology

Product Data Sheet

Certifications and Sustainable Features of EcoTouch[®] Insulation for MBI Plus Metal Building

- Certified by SCS Global Services to contain a minimum of 65% recycled glass content, 18% pre-consumer and 47% post-consumer.
- Certified to meet indoor air quality standards under the stringent GREENGUARD Indoor Air Quality Certification Program, and the GREENGUARD Gold Certification.

Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high-quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives. More information can be found at <http://sustainability.owenscorning.com>.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.SCSglobalservices.com.

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK[®]
www.owenscorning.com

Pub. No. 45109-H. Printed in U.S.A., December 2014. THE PINK PANTHER[™] & © 1964–2014 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2014 Owens Corning. All Rights Reserved.

